

HST-5400 Pen Leeb Hardness tester



Features

- Intelligent operation: Easy operation with several buttons, magnitude and Rockwell values displayed.
- Industrial bright OLED display: Good performance of OLED display, even in the sun shine.
- Accurate measurement value: high accuracy shown value error $\pm 0.5\%$ (HLD=800), showing the value of repeatability of 0.8%
- Supports a variety of hardness standards: HL, HV, HRA, HRC, HRB, HB, HV, HS
- Large capacity of data storage: Mass storage hitherto unknown, leading the technology trend. The retention of data to measure the hardness of 300 groups.
- Support "forged steel (Steel)" materials: Hardness values can be preset, limit, beyond the range of automatic alarm, convenient batch testing needs.

Technical Specification

Measuring range	(170-960)HLD,(17.9-69.5)HRC,(19-683)HB,(80-1042)HV,(30.6-102.6)HS,(59.188) HRA,(13.5-101.7)HRB
Hardness scale	HL,HB, HRB, HRC, HRA,HV, HS
Accuracy	HLD:±0.5% (800HLD)
Repeatability Value	HLD:0.8% (800HLD)
Resolution	128*64 OLED display
Power	Rechargeable lithium battery
Working Hours	About 10 hours
Operating temperature	0°C-40°C
Dimensions (mm)	148mm*30mm*25mm
Weight (g)	50

Standard Delivery

●Main unit	1
●Impact device type D	1
●Test block HLD	1
●Cleaning brush	1
●Adapter	1
●Supporting ring	
●Connecting cable	1
●Certificate	1
●Warranty card	1
●Instruction manual	1

HST GROUP Co., LTD.

NO. 4915, West Jingshi Road, Jinan 250012, PR CHINA.

Tel: +86-15910081986

www.hssdgroup.com - e-mail: admin@hssdtest.com