

HST-HX Low-temperature constant temperature circulator



Product Introduction

Widely used in universities, colleges, and enterprises in the fields of biology, chemical engineering, chemistry, pharmaceuticals, life sciences, and physical property testing. It provides users with a controlled, uniform, and constant temperature source for conducting constant temperature experiments or tests on experimental samples or manufactured products. It can also serve as a direct heating or cooling, or auxiliary heating or cooling heat source or cold source.

Technical Specifications:

Model	Temperature Range (°C)	Resolution (°C)	Fluctuation (±°C)	External Dimensions	Power (kw)	Volume (L)	Pump flow rate (L/min)	Head (m)
HX-08	0-100	0.01	0.05	320*370*675	1.3	8	13	3
HX-0508	-5-100		0.05		1.3			
HX-1008	-10-100		0.05		1.4			
HX-2008	-20-100		0.05	320*370*765	1.4			
HX-3008	-30-100		0.05	400*450*940	1.6			
HX-4008	-40-100		0.05		1.8			

HX-010	0-100		0.05		1.6			
HX-0510	-5-100		0.05		1.6			
HX-1010	-10-100		0.05	320*370*765	1.6			
HX-2010	-20-100		0.05		1.7	10	13	
HX-3010	-30-100		0.05	400*450*940	1.7			
HX-4010	-40-100		0.05	450*540*990	2.0			
HX-015	0-100		0.05		2.1			
HX-0515	-5-100		0.05		2.1			
HX-1015	-10-100		0.05	320*370*765	2.2			
HX-2015	-20-100		0.05		2.3	15	13	
HX-3015	-30-100		0.05	400*450*940	2.5			
HX-4015	-40-100		0.05	450*540*990	3.0			
HX-020	0-100		0.05		2.3			
HX-0520	-5-100		0.05		2.4			
HX-1020	-10-100		0.05	400*450*1040	2.5			
HX-2020	-20-100		0.05		2.6	20	13	
HX-3020	-30-100		0.05		2.8			
HX-4020	-40-100		0.05	450*540*1090	3.2			
HX-030	0-100		0.05		2.3			
HX-0530	-5-100		0.05		2.4			
HX-1030	-10-100		0.05	450*540*990	2.5			
HX-2030	-20-100		0.05		2.7			
HX-3030	-30-100		0.05		3.0	30	13	
HX-4030	-40-100		0.05	450*540*1090	3.5			

HST GROUP Co., LTD.

NO. 4915, West Jingshi Road, Jinan 250012, PR CHINA.

Tel: +86-15910081986

www.hssdgroup.com E-mail: admin@hssdtest.com